



PURESAN[®]

Bio Oxy Block



Puresan Bio Oxy Block is a solid form pure oxygen to be used as pre and post treatment with microbial water treatment products such as Puresan Bio Block, Puresan Bio Sewer and Puresan Bio Pond.

Application

- **Puresan Bio Oxy Block** is an environmentally + product that produces valuable pure oxygen as well as introducing much needed carbonates to ensure optimal biological action.
- **Puresan Bio Block** is a unique propriety block that allows aeration, oxygenation to enhance the biological treatment of stagnant, anaerobic and anoxic water. It is a product that has the ability to greatly enhance all aerobic biological action and results have shown dramatic oxidation of Ammonia, Hydrogen sulphide and significant reduction of solids.
- **Puresan Bio Oxy Blocks** provide the Oxygen is needed in conjunction with specialized organisms for the breakdown of Ammonia, hydrogen sulphide, FOG (Fat, Oil & Grease) as well as carbon-based organics.
- **Puresan Bio Oxy Blocks are used as follows:**
 One Oxy Block per 10,000L of water in relatively “clean” water environments, once a week.
 One Oxy Block per septic tank every month
 One Oxy Block per every 5 - 10 cubic meters in grease traps, once a week.



Find us on

Puresan Bio Oxy Blocks are available in containers of 20's



DISTRIBUTOR:



PURESAN[®]

Bio Oxy Block



Puresan Bio Oxy Block is a solid form pure oxygen to be used as pre and post treatment with microbial water treatment products such as Puresan Bio Block, Puresan Bio Sewer and Puresan Bio Pond.

Application

- **Puresan Bio Oxy Block** is an environmentally + product that produces valuable pure oxygen as well as introducing much needed carbonates to ensure optimal biological action.
- **Puresan Bio Block** is a unique proprietary block that allows aeration, oxygenation to enhance the biological treatment of stagnant, anaerobic and anoxic water. It is a product that has the ability to greatly enhance all aerobic biological action and results have shown dramatic oxidation of Ammonia, Hydrogen sulphide and significant reduction of solids.
- **Puresan Bio Oxy Blocks** provide the Oxygen is needed in conjunction with specialized organisms for the breakdown of Ammonia, hydrogen sulphide, FOG (Fat, Oil & Grease) as well as carbon-based organics.
- **Puresan Bio Oxy Blocks are used as follows:**
 One Oxy Block per 10,000L of water in relatively “clean” water environments, once a week.
 One Oxy Block per septic tank every month
 One Oxy Block per every 5 - 10 cubic meters in grease traps, once a week.



Find us on

Puresan Bio Oxy Blocks are available in containers of 20's



DISTRIBUTOR: